

1. Identification

Product identifier	PowerTrans TO-4 50		
Other means of identification	NM0245-031120		
Recommended use	Off-highway transmission lubricant		
Recommended restrictions	Not for food, drug, or household use.		
Manufacturer/Importer/Supplier/Distributor information			
Manufacturer			
Company name	Nemco Resources Ltd		
Address	25 Midland Street Winnipeg, MB R3E 3J6 Canada		
Telephone	Phone:	204-788-1030	
	Fax:	204-788-1593	
	Toll Free:	855-755-6737 (M-F 8am-4:30pm)	
Website	www.nemco.ca/msds-safety-information		
E-mail	info@nemco.ca		
Emergency phone number	NEMCO:	855-755-6737 (M-F 8am-4:30pm)	
Supplier	See above.		

2. Hazard identification

Physical hazards	Not classified.	
Health hazards	Reproductive toxicity	Category 2
Environmental hazards	Not classified.	

Label elements



Signal word	Warning	
Hazard statement	Suspected of damaging fertility or the unborn child.	
Precautionary statement		
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing, eye protection and face protection.	
Response	IF exposed or concerned: Get medical attention.	
Storage	Store locked up.	
Disposal	Dispose of container in accordance with local, regional, national and international regulations.	
Other hazards	None known.	
Supplemental information	None.	

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), hydrotreated heavy paraffinic		64742-54-7	60-80*
Distillates (petroleum), hydrotreated light paraffinic		64742-55-8	1-5*
Distillates (petroleum), solvent-dewaxed heavy paraffin		64742-65-0	1-5*
Petroleum distillates, solvent dewaxed light paraffinic		64742-56-9	1-5*
Phenol, Dodecyl-, Branched		121158-58-5	0.1-1*

Chemical name	Common name and synonyms	CAS number	%
Residual oils (petroleum), solvent-dewaxed		64742-62-7	10-30*

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments *CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.
Skin contact	Flush with cool water. Wash with soap and water. Obtain medical attention if irritation persists.
Eye contact	Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical attention if irritation persists.
Ingestion	Rinse mouth. Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Never give anything by mouth if victim is unconscious or is convulsing. Obtain medical attention.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical attention. If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Hazardous combustion products	May include and are not limited to: Oxides of carbon. Oxides of sulphur. Oxides of phosphorus.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Prevent entry into waterways, sewer, basements or confined areas. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground. Do not discharge into lakes, streams, ponds or public waters.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash thoroughly after handling. Use good industrial hygiene practices in handling this material. When using do not eat or drink.
--------------------------------------	--

8. Exposure controls/Personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	TWA	5 mg/m3	Inhalable fraction.
Petroleum distillates, solvent dewaxed light paraffinic (CAS 64742-56-9)	TWA	5 mg/m3	Inhalable fraction.
Residual oils (petroleum), solvent-dewaxed (CAS 64742-62-7)	TWA	5 mg/m3	Inhalable fraction.

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Petroleum distillates, solvent dewaxed light paraffinic (CAS 64742-56-9)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	1 mg/m3	Mist.

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	TWA	5 mg/m3	Inhalable fraction.
Petroleum distillates, solvent dewaxed light paraffinic (CAS 64742-56-9)	TWA	5 mg/m3	Inhalable fraction.
Residual oils (petroleum), solvent-dewaxed (CAS 64742-62-7)	TWA	5 mg/m3	Inhalable fraction.

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m3	Inhalable fraction.
Petroleum distillates, solvent dewaxed light paraffinic (CAS 64742-56-9)	TWA	5 mg/m3	Inhalable fraction.
Residual oils (petroleum), solvent-dewaxed (CAS 64742-62-7)	TWA	5 mg/m3	Inhalable fraction.

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Petroleum distillates, solvent dewaxed light paraffinic (CAS 64742-56-9)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)

Components	Type	Value
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	15 minute	10 mg/m3
	8 hour	5 mg/m3
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	15 minute	10 mg/m3
	8 hour	5 mg/m3
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	15 minute	10 mg/m3
	8 hour	5 mg/m3
Petroleum distillates, solvent dewaxed light paraffinic (CAS 64742-56-9)	15 minute	10 mg/m3
	8 hour	5 mg/m3

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Chemical respirator with organic vapour cartridge and full facepiece.

Skin protection**Hand protection**

Impervious gloves. Confirm with reputable supplier first.

Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. As required by employer code.

Respiratory protection	Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).
Thermal hazards	Not applicable.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. When using do not eat or drink.

9. Physical and chemical properties

Appearance	Viscous
Physical state	Liquid.
Form	Liquid.
Colour	Amber
Odour	Mild hydrocarbon
Odour threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	0.889
Solubility(ies)	
Solubility (water)	Insoluble
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	165 - 180 cSt @ 40°C
Other information	
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Do not mix with other chemicals.
Incompatible materials	Strong oxidising agents.
Hazardous decomposition products	May include and are not limited to: Oxides of carbon. Oxides of sulphur. Oxides of phosphorus.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May cause stomach distress, nausea or vomiting.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	> 5.2 mg/L, 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg, ECHA
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, ECHA
<i>Inhalation</i>		
LC50	Rat	> 5.5 mg/L, 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg, ECHA
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg, 24 Hours, ECHA > 2000 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	2.2 mg/L, 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg, ECHA
Petroleum distillates, solvent dewaxed light paraffinic (CAS 64742-56-9)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	> 5.2 mg/L, 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg, ECHA
Phenol, Dodecyl-, Branched (CAS 121158-58-5)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 15000 mg/kg
<i>Oral</i>		
LD50	Rat	2100 mg/kg, ECHA

Components	Species	Test Results
Residual oils (petroleum), solvent-dewaxed (CAS 64742-62-7)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	> 5.5 mg/L, 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg, ECHA
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Exposure minutes	Not available.	
Erythema value	Not available.	
Oedema value	Not available.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Corneal opacity value	Not available.	
Iris lesion value	Not available.	
Conjunctival reddening value	Not available.	
Conjunctival oedema value	Not available.	
Recover days	Not available.	
Respiratory or skin sensitisation		
Respiratory sensitisation	Not a respiratory sensitizer.	
Skin sensitisation	This product is not expected to cause skin sensitisation.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Contains < 3% (w/w) DMSO-extract See below.	
ACGIH Carcinogens		
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	A2 Suspected human carcinogen.	
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	A2 Suspected human carcinogen.	
Petroleum distillates, solvent dewaxed light paraffinic (CAS 64742-56-9)	A2 Suspected human carcinogen.	
Residual oils (petroleum), solvent-dewaxed (CAS 64742-62-7)	A2 Suspected human carcinogen.	
Canada - Manitoba OELs: carcinogenicity		
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	Suspected human carcinogen.	
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	Suspected human carcinogen.	
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	Suspected human carcinogen.	
Petroleum distillates, solvent dewaxed light paraffinic (CAS 64742-56-9)	Suspected human carcinogen.	
Residual oils (petroleum), solvent-dewaxed (CAS 64742-62-7)	Suspected human carcinogen.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	Volume 33, Supplement 7 - 3 Not classifiable as to carcinogenicity to humans.	
Reproductive toxicity	Suspected of damaging fertility or the unborn child.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.	
Further information	Not available.	

12. Ecological information

Ecotoxicity See below

Ecotoxicological data

Components		Species	Test Results
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)			
Crustacea	EC50	Daphnia	1000 mg/L, 48 Hours
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)			
Crustacea	EC50	Daphnia	1000 mg/L, 48 Hours
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)			
Crustacea	EC50	Daphnia	1000 mg/L, 48 Hours
Petroleum distillates, solvent dewaxed light paraffinic (CAS 64742-56-9)			
Crustacea	EC50	Daphnia	1000 mg/L, 48 Hours
Residual oils (petroleum), solvent-dewaxed (CAS 64742-62-7)			
Crustacea	EC50	Daphnia	1000 mg/L, 48 Hours
Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.		
Bioaccumulative potential			
Mobility in soil	No data available.		
Mobility in general	Not available.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

General	Canada: TDG Proof of Classification: Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.
Transportation of Dangerous Goods (TDG - Canada)	Not regulated as dangerous goods.


15. Regulatory information

Canadian federal regulations	This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.	
Export Control List (CEPA 1999, Schedule 3)	Not listed.	
Greenhouse Gases	Not listed.	
Precursor Control Regulations	Not regulated.	
WHMIS status	Hazardous	
International regulations		
Inventory status		
Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)		

16. Other information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	* 1
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X



Issue date

09-December-2021

Revision date

09-December-2021

Version No.

01

Other information

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.

Disclaimer

The information in the safety data sheet was written by Dell Tech Laboratories Ltd. (www.delltech.com) based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Prepared by

Dell Tech Laboratories Ltd. Phone: (519) 858-5021