

Catalys® ATF MD3

DESCRIPTION

Catalys ATF MD-3 is specially designed for automatic transmissions and applications that require a lubricant that meets outdated DEXRON III-H, ALLISON C-4 and MERCON specifications.

APPLICATION / BENEFITS

Catalys ATF MD-3 oil is recommended by GENERAL MOTORS and FORD. It is also recommended by import car manufacturers when the following standards are required: DEXRON II, DEXRON III, MERCON M2C 138-CJ and MERCON M2C 166-H.

Catalys ATF MD-3 can also be used in hydraulic systems where this type of fluid is accepted; its fluidity at low temperatures allows it to maintain its efficiency and promote equipment cold starts.

Composed of base oil and additives specific to this type of fluid, Catalys ATF MD-3 automatic transmission oil:

- is an excellent multigrade lubricant.
- resists oxidation and degradation while being compatible with commonly used elastomers.
- provides smooth gear changes with the addition of friction modifiers and prevents foaming.
- protects the transmission against wear and failure thanks to extreme pressure additives carefully selected

PHYSICAL PROPERTIES	ASTM METHOD	Catalys ATF MD3
Color		Red
Kinematic Viscosity at 40°C, cSt	D445	34,1
Kinematic Viscosity at 100°C, cSt	D445	7,0
Viscosity Index, min.	D2270	171
Density at 15°C, kg/L	D1298	0,850
Flash Point, °C	D92	171
Pour Point, °C	D97	-50

The values listed above are typical of current production, variations in these properties may occur.

AVAILABLE PACK SIZES

	Bulk	Drum	Keg	Pail
Catalys ATF MD3	07-1866-00	07-1866-05	07-1866-11	07-1866-10

THE PACK SIZES ABOVE ARE OUR STANDARD PACK SIZES. PLEASE COMMUNICATE WITH US TO FIND OUT FORMATS AVAILABLE LOCALLY.

HEALTH / SAFETY

GHS compliant English and French Safety Data Sheets are available at catalyslubricants.ca under 'Safety Data Sheets'. Keep container closed when not in use. Please refer to the SDS for safe handling information. Always take used oil and containers to an authorized collection point. Avoid discharge into the environment. As with any oil, keep out of reach of children and animals.

QUALITY

Catalys Lubricants partners with respected industry suppliers to bring you high quality products. For more information, contact your local Catalys Representative. Please ensure this product is right for the equipment by following the recommendations of the equipment operating manual.

CONTACT US

British Columbia	Alberta	Manitoba	Ontario	Quebec
7483 Progress Way	Unit 130, 16815 117 th Ave NW	25 Midland Street	3462 White Oak Road	2320, rue de la Métropole
Delta, BC	Edmonton, AB	Winnipeg, MB	London, ON	Longueuil, QC
V4G 1E7	T5M 3V6	R3E 3J6	N6E 2Z9	J4G 1E6
855.946.4226	877.222.8507	855.755.6737	800.673.6231	800.363.0590

Catalys® is a registered trademark of Entreprises Émile Crevier Inc.