

PROTECTAC

PROTECTAC 807 and 808: PREMIUM QUALITY UNDERCOATINGS

PROTECTAC 807 and 808 from Catalys are superior undercoating made from paraffinic mineral oil, rust, corrosion and oxidation inhibitors.

PROTECTAC 807 and 808 are non dripping undercoating, i.e., compare to conventional oil-based undercoating; they do not leave any oil spills on the ground after the application.

Because of their infiltrating and penetrating properties, **PROTECTAC 807 and 808** prevent rust in hard to reach locations. These undercoating products also possess good adhesion to metallic surfaces. Moreover, **PROTECTAC 807 and 808** have a pleasant scent.

All these characteristics and properties demonstrate that **PROTECTAC 807 and 808** is an exceptional product.

APPLICATION

Before the application, one must clean the surfaces in order to maximize the adhesion of the product, i.e., remove dirt, rust scale or petroleum based chemicals or by-products that may lead to dripping. The undercoating can be applied via a low pressure airless spray equipment (with additional adapters).

TYPICAL PROPERTIES FOR PROTECTAC 807 AND 808

PROPERTIES	ASTM TEST	PROTECTAC 807/808
Viscosity		
cSt at 40°C	D445	---
cSt at 100°C	D445	---
Density at 15,6°C, g/cm ³	D1298	0,89
Flash Point (COC), °C (°F)	D92	210 (410)
Copper corrosion at 100°C for 3 hours	D130	1
Rust assay		
distilled water	D665	pass
synthetic sea water	D665	pass
Appearance	---	GEL
Color	---	GREEN/BEIGE

ATTENTION

Like all petroleum base undercoating products, we highly recommend to avoid the application of undercoating on rubbers, plastics, fibers glass or all other kind of materials which do not need antirust protection. This product will not affect the paint. Avoid spraying the product directly on paint, even if it does not affect it.

We believe that technical information and recommendations contained herein to be reliable and accurate. Because the company have no control on the use or the way the product will be apply, our responsibility will be limited to the quality of the product only.

Available size

	20 L	60 L	205 L	TOTE
Protectac 807	28-6263-10	28-6263-11	28-6263-05	28-6263-02
Protectac 808	28-6264-10	28-6264-11	28-6264-05	28-6264-02